

3M Canada Company

1840 Oxford Street East, Post Office Box 5757

London, Ontario N6A 4T1

Medical Emergency Telephone: (519) 451-2500, Ext. 2222

Transportation Emergency Telephone (CANUTEC): (613) 996-6666



=====
Material Safety Data Sheet
=====

Document id : 05-6937-6 Issue date : 2008/09/09
Version : 18.00 Supersedes date : 2006/04/12

Copyright, 1997, 3M Canada Company. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Prepared by: Corporate Regulatory Services, 3M Canada Company
Telephone: (800) 364-3577, Fax: (800) 603-7758, Web Site: www.3M.ca

1 Product Identification

Tradename:

3M(TM) SILICONE LUBRICANT

Product ID:

CS-0406-1902-8 62-4678-0930-7 62-4678-0931-5 62-4678-4930-3

62-4678-4935-2 78-8033-2219-3

Intended Use of Product:

LUBRICANT

Division:

INDUSTRIAL ADHESIVES AND TAPES

2 Composition/Information on Ingredients

Ingredient Name	CAS Number	Percentage
ISOBUTANE	75-28-5	70 - 80
HEPTANE	142-82-5	15 - 25
POLY (DIMETHYLSILOXANE)	63148-62-9	3 - 7

NOTE:

Each percentage is expressed as the ratio of the weight of the ingredient to the weight of the controlled product.

3 Hazards Identification

Critical Hazards:

Liquid in aerosol container;

Extremely flammable liquid and vapour.

Frostbite: Signs/symptoms can include intense pain, clouding of the cornea, redness, swelling, and blindness.

Moderate Eye Irritation: Signs/symptoms may include redness, swelling, pain, tearing, and blurred or hazy vision.

Frostbite: Signs/symptoms can include intense pain, discoloration of skin, and tissue destruction.

May be absorbed following inhalation and cause target organ effects.

See Sections 7 and 11 for further information.

4 First Aid Measures

Instructions for Eye Contact:

Flush eyes with large amounts of water. If signs/symptoms persist, get medical attention.

Instructions for Skin Contact:

Wash affected area with soap and water. If signs/symptoms develop, get medical attention.

Instructions for Inhalation:

Remove person to fresh air. If signs/symptoms develop, get medical attention.

Instructions for Ingestion:

Do not induce vomiting. Get immediate medical attention.

5 Fire Fighting Measures

Flash point:

-45.6 C TCC Propellant

Lower Explosive Limit (%):

Approximately 1.5 % by volume

Upper Explosive Limit (%):

Approximately 8 % by volume

Autoignition temperature:

Not Available

Suitable Extinguishing Media:

Use fire extinguishers with class B extinguishing agents (e.g., dry chemical, carbon dioxide).

Exposure Hazards during Fire:

Closed containers exposed to heat from fire may build pressure and explode. Vapours may travel long distances along the ground or floor to an ignition source and flash back.

Combustion Products from Fire:

Carbon monoxide - During Combustion;

Carbon dioxide - During Combustion;

Fire Fighting Procedures:

Water may not effectively extinguish fire; however, it should be

used to keep fire-exposed containers and surfaces cool and prevent explosive rupture. Wear full protective equipment (Bunker Gear) and a self-contained breathing apparatus (SCBA).

NFPA: Health	2
NFPA: Fire	4
NFPA: Reactivity	0
NFPA: Unusual Reaction Hazard	none

6 Accidental Release Measures

Personal Precautions:

Refer to other sections of this MSDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment. Call 3M-HELPS line (1-800-364-3577) for more information on handling and managing the spill.

Spill Response:

Evacuate unprotected and untrained personnel from hazard area. The spill should be cleaned up by qualified personnel. Remove all ignition sources such as flames, smoking materials, and electrical spark sources. Use only non-sparking tools. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Warning! A motor could be an ignition source and could cause flammable gases or vapors in the spill area to burn or explode. Place leaking containers in a well-ventilated area, preferably in an exhaust hood, if available, or outdoors. Contain spill. For larger spills, cover drains and build dikes to prevent entry into sewer systems or bodies of water. Cover spill area with a fire-extinguishing foam. An aqueous film forming foam (AFFF) is recommended. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a toxic, corrosivity or flammability hazard. Collect as much of the spilled material as possible using non-sparking tools. Clean up residue with an appropriate solvent selected by a qualified and authorized person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and MSDS. Collect the resulting residue containing solution. Place in a metal container approved for transportation by appropriate authorities. Seal the container. Dispose of collected material as soon as possible.

7 Handling and Storage

Storage Requirements:

No data available.

Incompatible Materials:

Store away from acids;
Store away from oxidizing agents.
Store away from heat;
Store out of direct sunlight.

Ventilation:

No data available.

Fire Prevention:

Extremely flammable liquid and vapour. Ground containers securely when transferring contents. Wear low static or properly grounded shoes. Do not spray near flames or sources of ignition.

Explosion Prevention:

Keep away from heat, sparks, open flame, pilot lights and other sources of ignition.

Static Prevention:

Avoid static discharge.

Use Instructions:

Keep container tightly closed. Do not pierce or burn container, even after use. Avoid contact with oxidizing agents.

8 Exposure Controls/Personal Protection

Personal Protection

Eye Protection:

Avoid eye contact with vapours, mists, or spray.
The following should be worn alone or in combination, as appropriate, to prevent eye contact:
Safety glasses with side shields

Hand Protection:

Wear insulated gloves to protect against frostbite.
The following glove material(s) are recommended:
nitrile rubber;

Skin Protection:

Avoid prolonged or repeated skin contact.
Select and use gloves and/or protective clothing to prevent skin contact based on the results of an exposure assessment. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible materials.

Respiratory Protection:

Avoid breathing of vapours, mists or spray.
Select one of the following approved respirators based on airborne concentration of contaminants and in accordance with regulations:

Half facepiece or fullface air-purifying respirator with organic vapor cartridges.

Ingestion (Prevention):

Do not eat, drink or smoke when using this product. Wash exposed areas thoroughly with soap and water.

Keep out of the reach of children.

Recommended Ventilation:

Use with appropriate local exhaust ventilation.

Use with functioning spray booth or local exhaust.

Do not use in a confined area or areas with little or no air movement.

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below Occupational Exposure Limits and/or control mist, vapour, or spray. If ventilation is not adequate, use respiratory protection equipment.

Ingredient Exposure Data

ISOBUTANE (75-28-5)

LD50 (rat, oral)

No data available.

LC50 (rat, inhalation/4 hours)

No data available.

Exposure Limits


ACGIH: TWA 1000 ppm

HEPTANE (142-82-5)

LD50 (rat, oral)

> 15000 mg/kg

LC50 (rat, inhalation/4 hours)

 103 g/m3

Exposure Limits

ACGIH: TWA 400 ppm

ACGIH: TWA 1640 mg/m3

ACGIH: STEL 2050 mg/m3

ACGIH: STEL 500 ppm

POLY(DIMETHYLSILOXANE) (63148-62-9)

Specific Ingredient Data

No data available.

LD50 (rat, oral)

> 17 g/kg

LD50 (dermal, rabbit)

> 2 g/kg

LC50 (rat, inhalation/4 hours)

No data available.

Exposure Limits

No data available.

9 Physical and Chemical Properties

Physical form,Color,Odour:	Liquid; Liquid in aerosol container; transparent; very slight odour;
Odour Threshold:	No data available.
pH:	Not applicable
Boiling point/boiling range:	Compressed Gas;
Melting point/melting range:	Not Available
Vapour pressure:	No data available.
Water Solubility:	Nil
Specific gravity:	0.64 Water=1
Vapour density:	2.97 Air=1
Volatile organic compounds:	Approximately 95 % SCAQMD
Evaporation rate:	1.9 Water=1
Viscosity:	Not applicable
Percent Volatile:	Approximately 95 % by weight

10 Stability and Reactivity

Conditions to Avoid:
Heat;
Store out of direct sunlight.

Materials to Avoid:
Store away from acids;
Store away from oxidizing agents.

Hazardous Decomposition:
Carbon monoxide - During Combustion;
Carbon dioxide - During Combustion;

Stability and Reactivity:
Stable. Hazardous polymerization will not occur.

11 Toxicological Information

Effects from Eye Contact:
Frostbite: Signs/symptoms can include intense pain, clouding of the cornea, redness, swelling, and blindness.
Moderate Eye Irritation: Signs/symptoms may include redness, swelling, pain, tearing, and blurred or hazy vision.

Effects from Skin Contact:
Frostbite: Signs/symptoms can include intense pain, discoloration of skin, and tissue destruction.
Mild Skin Irritation: Signs/symptoms can include localized redness, swelling, and itching.

Effects from Inhalation:
Upper Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose

and throat pain.

Intentional concentration and inhalation may be harmful or fatal.
May be absorbed following inhalation and cause target organ effects.

Effects from Ingestion:

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, nausea, diarrhea and vomiting.

Sensitization Information:

No data available.

Carcinogenicity:

No data available.

Mutagenicity:

No data available.

Reproductive Effects:

No data available.

Component Based Information:

No data available.

Product Based Information:

No data available.

Other Effects & Information:

Central Nervous System (CNS) Depression: Signs/symptoms may include headache, dizziness, drowsiness, incoordination, nausea, slowed reaction time, slurred speech, giddiness, and unconsciousness.

12 Ecological Information

Environmental Data:

Ecotoxicity Data:

Not determined.

Ecofate Data:

Not determined.

13 Disposal Considerations

Product as Sold:

Incinerate in a permitted hazardous waste incinerator. Facility must be capable of handling aerosol cans. As a disposal alternative, dispose of waste product in a permitted hazardous waste facility. Dispose of empty product containers in a sanitary landfill. Recycle empty aerosol containers where available.

Product Packaging:

No data available.

Special Instructions:

Since regulations vary, consult applicable regulations or authorities before disposal.

14 Transport Information

Transportation of Dangerous Goods

TDG Classification: Consumer Commodity

Special Information:: Contact 3M for more information.

These transportation classifications are provided as a customer service. As the shipper YOU remain responsible for complying with all applicable laws and regulations, including proper transportation classification and packaging. 3M's transportation classifications are based on product formulation, packaging, 3M policies and 3M's understanding of applicable current regulations. 3M does not guarantee the accuracy of this classification information. This information applies only to transportation classification and not the packaging, labeling, or marking requirements. The original 3M package is certified for Canadian ground shipment only. If you are shipping by air or ocean, the package may not meet applicable regulatory requirements.

International Dangerous Goods Classification

15 Regulatory Information

WHMIS Classification: A, B5, D2B

NOTE:

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all the information required by the CPR.

Product Certifications:

The product on this MSDS, or all its components, is included on the following countries' chemical inventories, as noted:

TSCA - Toxic Substances Control Act (USA)

EINECS - European Inventory of Existing Commercial Chemical Substances

AICS - Australian Inventory of Chemical Substances

DSL - Domestic Substances List (Canada)

CICS - Chinese Inventory of Chemical Substances

PICCS - Philippines Inventory of Commercial Chemical Substances

16 Other Information

Reason for Reissue:

The following Sections and topics have been updated or revised:

Section 3 - Hazards Identification - Critical Hazards;

Section 4 - First Aid Measures;

Section 8 - Exposure Controls/Personal Protection;

Section 9 - Physical and Chemical Properties;

Section 13 - Disposal Considerations;

WHMIS Classification change

The information in this Material Safety Data Sheet (MSDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, STATUTORY OR OTHERWISE, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

---End---