

# MATERIAL SAFETY DATA SHEET

# 1. Product and Company Identification

**Product name** H251769

THERMOGRIP 6368-4 **MSDS** name 20LB CTN

Product name(s) covered See Section 16 for Product Names Covered.

CAS# Mixture

Hot Melt Adhesive Product use **Generic description EVA Based Formulation** 

**Manufacturer** Bostik, Inc.

> 11320 Watertown Plank Road Wauwatosa, WI 53226 U.S.A.

24 hour emergency

Telephone: 1-800-227-0332 assistance (Outside U.S.) 1-703-527-3887 **General assistance** Telephone: 1-414-774-2250 **MSDS** assistance Telephone: 1-414-607-1224

#### 2. Hazards Identification

**Emergency overview** Contact with this material can cause irritation to the skin, eyes and mucous membranes.

Contact with molten material will cause thermal burns.

Potential health effects

**Eyes** HOT MOLTEN material can cause irreversible eye injury and burns. Contact with SOLID

material may cause irritation with temporary redness with stinging and tearing.

Skin When it is heated, this material may cause thermal burns. **Inhalation** Inhalation of mist causes irritation of respiratory system.

**Ingestion** Ingestion causes irritation of upper respiratory system and gastrointestinal disturbance. Molten

material will produce burns to the gastrointestinal tract.

Fire and explosion This product will not ignite under normal situations but can be ignited in the extreme heat

associated with a fire. Vapors are lighter than air and should rise, accumulating in overhangs

and ceilings. In a fire situation, exposed containers may build up pressure and burst

explosively spewing hot material. Irritating and potentially harmful vapors may be released in

a fire or spill situation.

# 3. Composition / Information on Ingredients

The manufacturer lists no ingredients as hazardous according to OSHA 29 CFR 1910.1200.

#### 4. First Aid Measures

First aid procedures

Eye contact If hot product contacts eye, flush with water for at least 15 minutes and seek medical attention

immediately.

Skin contact If hot product contacts skin, cool under running water and get medical attention. Cool melted

product on skin with plenty of water. Do not remove solidified product.

**Inhalation** Move to fresh air in case of accidental inhalation of vapours or decomposition products. If

symptoms persist, get medical attention.

Ingestion If ingested, get immediate medical attention. Do not induce vomiting unless instructed to do so

by medical personnel. Never give anything by mouth to a victim who is unconscious or is

having convulsions.

### 5. Fire Fighting Measures

**Hazardous combustion** 

products

Upon decomposition, this product emits carbon monoxide, carbon dioxide and/or low

molecular weight hydrocarbons.

Material name: H251769 MSDS US 45038 Version #: 06 Revision date: 01-24-2010 Print date: 01-24-2010

Extinguishing media

Suitable extinguishing

media

Dry chemical, foam, carbon dioxide. A solid stream of water may scatter molten product.

Fire fighting

Firefighters should wear full protective clothing including self contained breathing apparatus.

equipment/instructions

**Dust explosion hazard** None Known Sensitivity to static discharge

**Unusual fire & explosion** 

hazards

None Known

Do not use water on molten adhesive to avoid splattering and spreading of fire.

Flash point > 200 °F (> 93.3 °C)

### **6. Accidental Release Measures**

**Emergency action** Wear appropriate protective equipment and clothing during clean-up. Follow all Local, State,

Federal and Provencial regulations for disposal.

**Containment procedures** Isolate spill area. Stop discharge if safe to do so. Pellet or chip spill: Collect and contain for

salvage or disposal. Molten adhesive spill: Placard hot material, allow to cool and remove. Collect and contain for salvage or disposal. Stop material from contaminating soil or from

entering sewers or water streams.

See Federal reporting requirements listed in Section 15. We recommend you contact local Reporting

authorities to determine if there may be other local reporting requirements.

## 7. Handling and Storage

For Commercial Use Only - Not Packaged or Labeled for Home Use!

Handling Avoid contact with skin and eyes. Avoid contact with molten material. Wash thoroughly after

handling. Avoid breathing fumes if this product is used at high temperatures. Use this product

with adequate ventilation.

Keep the container tightly closed and dry. Storage

Attention! Follow label warnings even after container is emptied since empty containers may **Empty container precaution** 

retain product residues. Do not reuse empty container without professional cleaning for food, clothing, or products for human or animal consumption, or where skin contact can occur.

## 8. Exposure Controls / Personal Protection

Ventilation should be sufficient to effectively remove and prevent buildup of any dusts or fumes **Engineering controls** 

that may be generated during handling or thermal processing.

Personal protective equipment

**Eye protection** Wear safety glasses; chemical goggles for fumes which may arise from thermal processing.

Wear chemical goggles; face shield (if handling molten material).

Work clothing sufficient to prevent all skin contact should be worn, such as coveralls and long Skin and body protection

sleeves. For molten product, use any type rubber thermal insulating gloves and other clothing

as necessary to protect from thermal burns.

Respiratory protection When dusts or thermal processing fumes are generated and ventilation is not sufficient to

effectively remove them, appropriate NIOSH/MSHA approved respiratory protection must be

provided.

General Eye wash fountain and emergency showers are recommended.

### 9. Physical & Chemical Properties

**Target solids** 100 % pН N/A Density 0.94 g/cc Odor Mild

Light Amber Color Solid **Physical state** Freeze protect No

Material name: H251769 MSDS US 2/4

45038 Version #: 06 Revision date: 01-24-2010 Print date: 01-24-2010

## 10. Chemical Stability & Reactivity Information

Hazardous

reactions/decomposition

products

Upon decomposition, this product emits carbon monoxide, carbon dioxide and/or low

molecular weight hydrocarbons.

**Hazardous polymerization** 

**Conditions to avoid** 

Stability

Will not occur.

Do not add water or other volatile material to molten adhesive. Avoid excessive overheating. Stable under normal conditions. This product may react with strong acids, bases and oxidizing

agents.

# 11. Toxicological Information

**Carcinogenicity** If this product contains any carcinogens, they will be noted below:

## 12. Ecological Information

Bostik's hot melt adhesives are manufactured without the intentional use of volatile organic compounds and/or hazardous air pollutants regulated by the EPA in the Clean Air Act Amendment of 1990.

**Ecotoxicological information** No data available for this product.

# 13. Disposal Considerations

It is the obligation of each user of the product mentioned herein to determine and comply with the requirements of all applicable local, state and federal regulations.

Waste disposal

Dispose of waste material according to Local, State, Federal, and Provincial Environmental

Regulations.

# 14. Transport Information

#### DOT

Not regulated as hazardous goods.

#### **IATA**

Not regulated as hazardous goods.

#### **IMDG**

Not regulated as hazardous goods.

## 15. Regulatory Information

This MSDS is prepared and distributed pursuant to the Federal Hazard Communication Standard, 29 CFR 1910.1200

The product(s) covered by this M(SDS) do not include any of the 15 substances in the Candidate List of Substances of Very High Concern (SVHC) for authorization published by ECHA on October 28, 2008 or the list of 15 substances proposed on August 31, 2009 or the list of 14 substances proposed on January 13, 2010 above a concentration of 0.1% weight by weight (w/w).

**Federal regulations** All components are on the U.S. EPA TSCA Inventory List.

**State regulations**This product may contain an ingredient(s) known to the State of California to cause cancer,

birth defects, and/or other reproductive harm. If any of the ingredients in this product are subject to the Proposition 65 regulations they will be listed as such on the product label.

**International regulations**This product has been classified in accordance with the hazard criteria of the Controlled

Products Regulations and contains all the information required by the Controlled Products

Regulations.

**HMIS Ratings** Health: 1

Flammability: 1 Physical hazard: 0 Personal protection: X Immediate Hazard - No

SARA 311/312 HAZARD CATEGORIES

Delayed Hazard - No Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No

Material name: H251769 MSDS US

WHMIS status Non-controlled

#### 16. Other Information

**Disclaimer** The data in this MSDS has been compiled from publicly available sources. This data relates

only to the designated product and not to the use of said product in combination with other materials. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards which exist. Responsibility for proper precautions and safe use of the product lies with the user. All data in this MSDS is typical of the product as a whole, and does not represent any individual lot or batch, therefore, Bostik, Inc. makes no warranty about the accuracy of the data herein and assumes no liability for the use of such data. It is the responsibility of the user to comply with all applicable federal, state, and local laws and regulations.

Issue date01/24/2010Prepared byDavid PriebeSupercedes05/22/2006

This data sheet contains changes from the previous version in section(s):

This document has undergone significant changes and should be reviewed in its entirety.

Material name: H251769 MSDS US

45038 Version #: 06 Revision date: 01-24-2010 Print date: 01-24-2010