


HEALTH	0
FLAMMABILITY	1
REACTIVITY	0
PPI	NA

MATERIAL SAFETY DATA SHEET



Petro-Tape

NFPA SYMBOL

HMIS SYMBOL

Identification of the Substance / Preparation and Company

Product Name: Petro-Tape
 Chemical Family: Processed polymer
 Use: Thread sealing tape

Manufacturer/Supplier: Jet-Lube of Canada Ltd.
 Address: 3820 - 97 Street
 Edmonton, Alberta
 Canada T6E 5S8
 Phone: (780) 463-7441 Fax: (780) 463-7454
 CCOHS: 1-800-263-8466 Emergency: (713) 674-7617

Composition Information on Ingredients

Hazardous Components: None
 CAS No:
 Wt%:
 OSHA PEL:
 ACGIH TLV:
 Other:

Hazards Identification

Eyes: Mechanical irritation.
 Inhalation: N/A
 Ingestion: Has been shown to be inert when ingested by rats.
 Skin: Probably non-irritating and non-absorbing

First Aid Measures

Eyes: Flush with water until all residual material is gone. If irritation persists, seek medical help.
 Inhalation: N/A
 Ingestion: Allow to pass normally.
 Skin: No special measures required.

Fire Fighting Measures

Extinguishing Media: Foam, dry chemical, halon, carbon dioxide, sand, earth or water mist.
 Unsuitable Extinguishing Media: Water jet.
 Protective Equipment: Self-contained breathing apparatus.

Accidental Release Measures

Personal Precautions: None required
 Environmental Precautions: Avoid disposal into drains.
 Spillage: Sweep up excess to avoid a walking hazard.

Handling and Storage

No special handling precautions necessary.

Exposure Control / Personal Protection

Respiratory Protection: None required
 Hand Protection: None required
 Eye Protection: None required
 Body Protection: None required

Prepared by: Jet-Lube of Canada Ltd.
 Date Issued: October 1, 2001

Physical and Chemical Properties

Physical State: Solid tape Odor: None
 Boiling Point: N/A pH: Neutral
 Melting Point: 341°C (642°F) Water Solubility: Nil
 Flash Point (COC): N/A
 Specific Gravity (H₂O = 1): 2.1 - 2.2
 Oxidizing Properties: None % Volatiles: Nil
 Flammability: Nil at ambient temp. OAR Value: N/A
 Explosive Properties: N/A
 Evaporation Rate: (Butyl Acetate = 1.0): <0.01

Stability and Reactivity

Stability: Chemically stable under normal conditions
 Conditions to Avoid: Heating above 750°F for prolonged periods.
 Materials to Avoid: Molten alkali metals, interhalogen compounds
 Hazardous Decomposition Products: Smoke, tetrafluoroethylene above 800°F, hexafluoropropylene above 825°F, perfluoroisobutylene above 885°F, Carbonyl Fluoride above 930°F.

Toxicological Information

Inhalation: N/A Skin Irritancy: None
 Chronic Toxicity: None known
 Genotoxicity: None known
 Carcinogen - NTP: No IARC: No OSHA: No

Ecological Information

Possible Effects: None known
 Behavior: Relatively well behaved.
 Environmental Fate: Highly unlikely to cause noticeable contamination. Non-toxic to marine or land organisms.

Waste Disposal

Consult federal, provincial and local regulations for disposal of petroleum products.

Transport Information

Not classified as hazardous for transport.
 D.O.T: Non-hazardous
 UN No: N/A Air Transport (ICAO): N/A
 Sea Transport (IMO & IMDG): N/A
 Road & Rail Transport (ADR/RID): N/A

Regulatory Information

WHMIS: Not regulated TDG: Not regulated
 Labelling Requirements: None
 DSL: All components listed TSCA: All components listed
 R Phrases: None applicable, as known
 S Phrases: None applicable, as known
 SARA 313: N/A
 Ozone Depleting Chemicals: None

Other Information

As of issue date, the information contained herein is accurate and reliable to the best of Jet-Lube's knowledge. Jet-Lube does not warrant or guarantee its accuracy or reliability and shall not be liable for any loss or damage arising out of the use thereof. It is the users' responsibility to satisfy themselves that the information offered for their consideration is suitable for their particular use.