


MATERIAL SAFETY DATA SHEET

L-59E

NFPA Hazard Rating



0 = Minimum 1 = Light 2 = Moderate 3 = Serious 4 = Extreme

Section 1 - Product Identification

J. WALTER COMPANY LTD. 5977 Transcanada Highway Pointe-Claire, Quebec H9R 1C1 Emergency: CANUTEC (613) 996-6666	Trade name: E-NOX Clean Product description: High strength stainless steel cleaner Order no.: 53-G 303, 53-G 306, 53-G 307, 53-G 308 WHMIS Classification: D2B, E Controlled under WHMIS: Yes
---	--

Section 2 - Hazardous Ingredients

<u>Ingredients</u>	<u>CAS Number</u>	<u>% by Weight</u>	<u>LD₅₀RAT (Oral)</u>	<u>LC₅₀RAT</u>
Phosphoric Acid	7664-38-2	10-30	1530 mg/kg	N/Av
Linear Alkyl Benzene Sulphonate	68411-30-3	1-5	1470 mg/kg	N/Av

Section 3 - Physical / Chemical Characteristics

Physical state: Gel	Odour & appearance: Characteristic odor, yellow	Odour threshold: N/Av
pH (at 50g/L H₂O): 1.5	Boiling point: 98°C	Freezing point: 0°C
Density: 1,10 g/ml	Vapour pressure: N/Av	Vapour density: N/Av
Evaporation rate: N/Av	VOC (g/L): 0	Water solubility: Soluble

Section 4 - Fire & Explosion Hazard

Flammability: No	Conditions: None	Extinguishing media: N/A
Flashpoint: N/A		Hazardous combustion products: None
Auto ignition temperature: N/A		Sensitivity to mechanical impact or static discharge: N/A
Flammable limits (%): Upper: N/A Lower: N/A		

Section 5 - Reactivity Data

Chemical stability: Yes **Conditions:** None
Reactivity conditions: None
Incompatible substances: Strong alkaline.
Hazardous decomposition products: If mixed with cleaners containing chlorides, chlorine will be set free.

MATERIAL SAFETY DATA SHEET

L-59E

Section 6 - Toxicological Data

Route of entry: Eye and skin contact, inhalation, ingestion.

Acute exposure effects: Contact with eyes, skin and mucosal tissues could cause irritation.

Chronic exposure effects: None

Exposure limits (TLV/PEL): N/Av

Carcinogenicity

No

Mutagenicity

No

Reproductive toxicity

No

Teratogenicity

No

Synergistic effects

No

If yes to any of the above, specify:

Section 7 - Preventive Measures

Protective equipment: Eyewear, gloves.

Handling procedures: Keep containers tightly closed.

Waste disposal methods: Dispose as per municipal, provincial and federal regulations.

Leak/spill procedures: Soak up with absorbent material. Rinse small amounts with water. Neutralize with Surfox-N (54-A 023), UNO S (53-G 033) or UNO S F (53-G 023).

Storage requirements: Store below 50°C, protect from freezing.

Engineering controls: Ensure adequate ventilation.

Handling equipment: None

Special shipping information: Corrosive liquid, acidic, inorganic, N.O.S.(Phosphoric acid), Class 8, UN 3264, P.G.III

Section 8 - First Aid Measures

Skin contact: Wash gently and carefully with warm water for 30 minutes or until product is completely off skin. Remove contaminated clothing, shoes and leather articles and wash before re-using. Consult a physician.

Eye contact: Immediately rinse exposed eyes by maintaining eyelids opened under light warm running water for 30 minutes or until product is eliminated. Avoid exposing the eyes or face to rinsing water. Consult a physician immediately.

Inhalation: Remove patient to fresh air.

Ingestion: Do not induce vomiting. Rinse mouth and drink plenty of water. Consult a physician immediately.

Section 9 - Preparation of MSDS

Prepared by: International Product Manager - Chemical Tools

Telephone: 1-888-592-5837

Date: October 12, 2009

This data is offered in good faith as typical values and not as a product specification. No warranty, either express or implied is hereby made. The recommended industrial hygiene and safe handling procedures are believed to be generally applicable. However, each user should review these recommendations in the specific context of the intended use and determine whether they are appropriate.

N/A - Not Applicable

N/Av - Not Available