



**SCS1002 12C-Crtrg (0.730 Lbs-0.331 Kg)**  
**Silicone Rubber Sealant**

**1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION**

**Manufactured By:** Waterford Plant  
260 Hudson River Rd  
Waterford NY 12188

**Revised:** 06/12/2009  
**Preparer:** PRODUCT STEWARDSHIP COMPLIANCE AND STANDARDS  
**CHEMTREC** 1-800-424-9300  
**MSDS Contact** 304-652-8334  
**Information** Regulatory.Questions@momentive.com

**Chemical Family/Use:** Sealant  
**Formula:** Mixture

**HMIS**

Flammability: 1      Reactivity: 0      Health: 1

**NFPA**

Flammability: 1      Reactivity: 0      Health: 1

**2. HAZARDS IDENTIFICATION**

**WHMIS HAZARD CLASS**



Very Toxic Material Causing Other Toxic Effects  
Toxic Material Causing Other Toxic Effects

**EMERGENCY OVERVIEW**

WARNING! Irritating to eyes, respiratory system and skin. May be harmful if swallowed. May cause liver damage. Contains octamethylcyclotetrasiloxane which may cause reproductive effects based on animal data.

Form: solid      Color: white      Odor: Acetic acid.

**POTENTIAL HEALTH EFFECTS**

**INGESTION**

May be harmful if swallowed.

**SKIN**

May cause mild skin irritation.

**INHALATION**

None known.



**SCS1002 12C-Crtrg (0.730 Lbs-0.331 Kg)**  
**Silicone Rubber Sealant**

**EYES**

May cause mild eye irritation.

**MEDICAL CONDITIONS AGGRAVATED**

None known.

**SUBCHRONIC (TARGET ORGAN )**

Liver injury may occur.; Reproductive hazard

**CHRONIC EFFECTS / CARCINOGENICITY**

This product or one of its ingredients present at 0.1% or more is NOT listed as a carcinogen or suspected carcinogen by NTP, IARC, or OSHA.

**ROUTES OF EXPOSURE**

Dermal; Eyes

**3. COMPOSITION/INFORMATION ON INGREDIENTS**

**HAZARDOUS COMPONENTS**

<u>PRODUCT COMPOSITION</u>	<u>CAS REG NO.</u>	<u>WGT. %</u>
METHYLTRIACETOXYSILANE	4253-34-3	1 - 5 %
Octamethylcyclotetrasiloxane	556-67-2	1 - 5 %
Titanium Dioxide	13463-67-7	1 - 5 %

Note(s): See Section 15 for HMIRC information.

**4. FIRST AID MEASURES**

**INGESTION**

Do not induce vomiting. If victim is conscious, give 1-3 glasses of water to drink. Never give anything by mouth to an unconscious person. Get medical attention if irritation persists.

**SKIN**

To clean from skin, remove completely with a dry cloth or paper towel, before washing with detergent and water. If skin irritation persists, call a physician.

**INHALATION**

If inhaled, remove to fresh air. If not breathing give artificial respiration using a barrier device. If breathing is difficult give oxygen. Get medical attention.



**SCS1002 12C-Crtrg (0.730 Lbs-0.331 Kg)**  
**Silicone Rubber Sealant**

**EYES**

In case of contact, immediately flush eyes with plenty of water for at least 15 minutes and get medical attention if irritation persists.

**NOTE TO PHYSICIAN**

Treatment is symptomatic and supportive.

**5. FIRE-FIGHTING MEASURES**

**FLASH POINT:** > 93.3 °C; 200 °F  
**METHOD:** estimated  
**AUTOIGNITION TEMPERATURE:** none  
**FLAMMABLE LIMITS IN AIR - LOWER (%):** not applicable  
**FLAMMABLE LIMITS IN AIR - UPPER (%):** not applicable

**SENSITIVITY TO MECHANICAL IMPACT:** No

**SENSITIVITY TO STATIC DISCHARGE**

Sensitivity to static discharge is not expected.

**EXTINGUISHING MEDIA**

All standard extinguishing agents are suitable.

**SPECIAL FIRE FIGHTING PROCEDURES**

Firefighters must wear NIOSH/MSHA approved positive pressure self-contained breathing apparatus with full face mask and full protective clothing.

**6. ACCIDENTAL RELEASE MEASURES**

**ACTION TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED**

Wipe, scrape or soak up in an inert material and put in a container for disposal. Wash walking surfaces with detergent and water to reduce slipping hazard. Wear proper protective equipment as specified in the protective equipment section.

**7. HANDLING AND STORAGE**

**PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE**

Product releases acetic acid during application and curing. Use mechanical ventilation to stay below TLV of 10 ppm acetic acid. Avoid contact with skin, eyes and clothing. Avoid accidental ingestion of this material. Wash hands and face before eating, drinking, smoking, using toilet facilities, or applying cosmetics. Remove contact lenses before using sealant. Do not handle lenses until all sealant has been cleaned from the fingertips, nails and cuticles. Residual sealant may remain on fingers for



**SCS1002 12C-Crtrg (0.730 Lbs-0.331 Kg)**  
**Silicone Rubber Sealant**

several days and transfer to lenses and cause severe eye irritation. Store away from heat, sources of ignition, and incompatibles. Keep away from children. Keep container closed when not in use.

**STORAGE**

Store away from heat, sources of ignition, and incompatibles. Keep out of the reach of children. Keep container tightly closed.

**8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

**ENGINEERING CONTROLS**

Eyewash stations; Showers; Exhaust ventilation

**RESPIRATORY PROTECTION**

If exposure limits are exceeded or respiratory irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Supplied air respirators may be required for non-routine or emergency situations. Respiratory protection must be provided in accordance with OSHA regulations (see 29CFR 1910.134).

**PROTECTIVE GLOVES**

Impermeable or chemical resistant gloves.

**EYE AND FACE PROTECTION**

Safety glasses with side-shields

**OTHER PROTECTIVE EQUIPMENT**

Wear suitable protective clothing and eye/face protection.

**Exposure Guidelines**

<u>Component</u>	<u>CAS RN</u>	<u>Source</u>	<u>Value</u>
------------------	---------------	---------------	--------------

Consult local authorities for acceptable provincial values.

Absence of values indicates none found

PEL - OSHA Permissible Exposure Limit; TLV - ACGIH Threshold Limit Value; TWA - Time Weighted Average

OSHA revoked the Final Rule Limits of January 19, 1989 in response to the 11th Circuit Court of Appeals decision (AFL-CIO v. OSHA) effective June 30, 1993. See 29 CFR 1910.1000 (58 FR 35338).

**9. PHYSICAL AND CHEMICAL PROPERTIES**

<b>BOILING POINT - C &amp; F:</b>	no data available
<b>VAPOR PRESSURE (20 C) (MM HG):</b>	no data available
<b>VAPOR DENSITY (AIR=1):</b>	no data available
<b>FREEZING POINT:</b>	no data available
<b>PHYSICAL STATE:</b>	solid



**SCS1002 12C-Crtrg (0.730 Lbs-0.331 Kg)**  
**Silicone Rubber Sealant**

<b>ODOR:</b>	Acetic acid.
<b>ODOR THRESHOLD:</b>	no data available
<b>COLOR:</b>	white
<b>EVAPORATION RATE (BUTYL ACETATE=1):</b>	no data available
<b>SPECIFIC GRAVITY (WATER=1):</b>	no data available
<b>DENSITY:</b>	ca. 1.040 g/cm <sup>3</sup>
<b>pH:</b>	no data available
<b>VOLATILE ORGANIC CONTENT (VOL):</b>	1.5 %(m)
<b>SOLUBILITY IN WATER (20 C):</b>	insoluble
<b>SOLUBILITY IN ORGANIC SOLVENT (STATE SOLVENT):</b>	Soluble in toluene
<b>PARTITION COEFFICIENT: N-OCTANOL/WATER:</b>	no data available
<b>VOC EXCL. H<sub>2</sub>O &amp; EXEMPTS (G/L):</b>	20

**10. STABILITY AND REACTIVITY**

**STABILITY**  
Stable

**HAZARDOUS POLYMERIZATION**  
Will not occur.

**HAZARDOUS THERMAL DECOMPOSITION / COMBUSTION PRODUCTS**

Carbon monoxide; Carbon dioxide (CO<sub>2</sub>); Silicon dioxide.; formaldehyde; This product contains methylpolysiloxanes which can generate formaldehyde at approximately 300 degrees Fahrenheit (150°C) and above, in atmospheres which contain oxygen. Formaldehyde is a skin and respiratory sensitizer, eye and throat irritant, acute toxicant, and potential cancer hazard. A MSDS for formaldehyde is available from Momentive.

**INCOMPATIBILITY (MATERIALS TO AVOID)**  
none

**CONDITIONS TO AVOID**  
None known.

**11. TOXICOLOGICAL INFORMATION**

**ACUTE ORAL**  
Remarks: Unknown

**Repeated dose toxicity**  
none

**ACUTE DERMAL**  
Remarks: Unknown



**SCS1002 12C-Crtrg (0.730 Lbs-0.331 Kg)**  
**Silicone Rubber Sealant**

---

**ACUTE INHALATION**

Remarks: NONE FOUND

**OTHER**

Octamethylcyclotetrasiloxane Ingestion: Rodents given large doses via oral gavage of octamethylcyclotetrasiloxane (1600 mg/kg day, 14 days) developed increased liver weights relative to unexposed control animals due to hepatocellular hyperplasia (increased number of liver cells which appear normal) as well as hypertrophy (increased cell size). Inhalation: In inhalation studies, laboratory rodents exposed to octamethylcyclotetrasiloxane (300 ppm five days week, 90 days) developed increased liver weights in female animals relative to unexposed control animals. When the exposure was stopped, liverweights returned to normal. Microscopic examination of the liver cells did not show any evidence of pathology. Inhalation studies utilizing laboratory rabbits and guinea pigs showed no effects on liver weights. Inhalation exposures typical of industrial usage (5-10 ppm) showed no toxic effects in rodents. Range finding reproductive studies were conducted (whole body inhalation, 70 days prior to mating, through mating, gestation and lactation) with octamethylcyclotetrasiloxane (D4). Rats were exposed to 70 and 700 ppm. In the 700 ppm group, there was a statistically significant reduction in mean litter size and in implantation sites. No D4 related clinical signs were observed in the pups and no exposure related pathological findings were found. Interim results from a two generation reproductive study in rats exposed to 500 and 700 ppm D4 (whole body inhalation, 70 days prior to mating, through mating, gestation and lactation) resulted in a statistically significant decrease in live mean litter size as well as extended periods of off-spring delivery (dystocia). These results were not observed at the 70 and 300 ppm dosing levels. Preliminary results from an ongoing 24-month combined chronic/oncogenicity study in rats exposed to 10, 30, 150, or 700 ppm D4 showed test-article related effects in the kidney (male and female) and uterus of rats exposed for 12 to 24 months. These effects include increased kidney weight and severity of chronic nephropathy, increased uterine weight, increased incidence of endometrial cell hyperplasia, and an increased incidence of endometrial adenomas. All of these effects are limited to the 700 ppm exposure group. These results have been shown to be rat-specific. Further studies are ongoing. In developmental toxicity studies, rats and rabbits were exposed to octamethylcyclotetrasiloxane at concentrations up to 700 ppm and 500 ppm respectively. No teratogenic effects (birth defects) were observed in either study.

**GENETIC TOXICITY IN VITRO**

none

**GENETIC TOXICITY IN VIVO**

none

**SENSITIZATION**

no data available

**SKIN IRRITATION**

no data available

**EYE IRRITATION**

no data available

**MUTAGENICITY**

Unknown



**SCS1002 12C-Crtrg (0.730 Lbs-0.331 Kg)**  
**Silicone Rubber Sealant**

**12. ECOLOGICAL INFORMATION**

**ECOTOXICITY**

no data available

**DISTRIBUTION**

no data available

**CHEMICAL FATE**

no data available

**13. DISPOSAL CONSIDERATIONS**

**DISPOSAL METHOD**

Disposal should be made in accordance with federal, state and local regulations.

**14. TRANSPORT INFORMATION**

**Further Information:**

This product is not regarded as dangerous goods according to the national and international regulations on the transport of dangerous goods.

**15. REGULATORY INFORMATION**

**Inventories**

Canada NDSL Inventory	n (Negative listing)
Japan Inventory of Existing & New Chemical Substances (ENCS)	y (positive listing)
Korea Existing Chemicals Inventory (KECI)	y (positive listing)
China Inventory of Existing Chemical Substances	y (positive listing)
Australia Inventory of Chemical Substances (AICS)	y (positive listing)
EU list of existing chemical substances	y (positive listing)
Philippines Inventory of Chemicals and Chemical	y (positive listing)



**SCS1002 12C-Crtrg (0.730 Lbs-0.331 Kg)**  
**Silicone Rubber Sealant**

---

Substances (PICCS)

TSCA list

y (positive listing)

On TSCA Inventory

Canada DSL Inventory

q (quantity restricted)

For inventories that are marked as quantity restricted or special cases, please contact Momentive.

**Canadian Regulatory Information**

**WHMIS HAZARD CLASS**

Very Toxic Material Causing Other Toxic Effects, Toxic Material Causing Other Toxic Effects

**CPR Compliance**

This product has been classified according to the hazard criteria of the CPR and the MSDS contains all of the information required by the CPR.

**US Regulatory Information**

**Other**

**SCHDLE B/HTSUS:**

3214.10.00.10 Mastic based on rubber

**ECCN:**

EAR99

**16. OTHER INFORMATION**

**OTHER**

These data are offered in good faith as typical values and not as product specifications. No warranty, either expressed or implied, is made. The recommended industrial hygiene and safe handling procedures are believed to be generally applicable. However, each user should review these recommendations in the specific context of the intended use and determine whether they are appropriate., C = ceiling limit NEGL = negligible EST = estimated NF = none found  
NA = not applicable UNKN = unknown NE = none established REC = recommended ND = none determined V = recommended by vendor SKN = skin TS = trade secret R = recommended MST = mist NT = not tested STEL = short term exposure limit ppm = parts per million ppb = parts per billion By-product= reaction by-product, TSCA inventory status not required under 40 CFR part 720.30(h-2).