



**SCS1203 12R-Crtrg (0.730 Lbs-0.331 Kg)**  
**Silicone sealant (adhesive)**

**1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION**

**Manufactured By:** Waterford Plant  
260 Hudson River Rd  
Waterford NY 12188

**Revised:** 09/05/2007

**Preparer:** PRODUCT STEWARDSHIP COMPLIANCE AND STANDARDS  
**CHEMTREC** 1-800-424-9300

**Chemical Family/Use:** Sealant  
**Formula:** MixtureSilicone sealant

**HMIS**

Flammability: 1      Reactivity: 0      Health: 2

**NFPA**

Flammability: 1      Reactivity: 0      Health: 2

**2. HAZARDS IDENTIFICATION**

**EMERGENCY OVERVIEW**

WARNING! Irritating to eyes, respiratory system and skin. May be harmful if swallowed. Adverse liver and reproductive effects reported in animals. Attention: Not for injection into humans.

Form: Solid      Color: Black      Odor: vinegar-like

**POTENTIAL HEALTH EFFECTS**

**INGESTION**

May be harmful if swallowed.

**SKIN**

May cause mild skin irritation.

**INHALATION**

None known.

**EYES**

May cause mild eye irritation.

**MEDICAL CONDITIONS AGGRAVATED**

None known.

**SUBCHRONIC (TARGET ORGAN )**

Liver injury may occur.; Reproductive hazard.

**CHRONIC EFFECTS / CARCINOGENICITY**

This product or one of its ingredients present at 0.1% or more is NOT listed as a carcinogen or suspected carcinogen by NTP, IARC, or OSHA.



**SCS1203 12R-Crtrg (0.730 Lbs-0.331 Kg)**  
**Silicone sealant (adhesive)**

**ROUTES OF EXPOSURE**  
Dermal; Eyes

**3. COMPOSITION / INFORMATION ON INGREDIENTS**

<u>PRODUCT COMPOSITION</u>	<u>CAS REG NO.</u>	<u>WGT. %</u>
<b><u>A. HAZARDOUS</u></b>		
METHYLTRIACTOXYSILANE	4253-34-3	1 - 5 %
Octamethylcyclotetrasiloxane	556-67-2	1 - 5 %
<b><u>B. NON-HAZARDOUS</u></b>		
Siloxanes & Silicones, Dimethylpolymers w/Methylsilsequioxanes	68554-67-6	10 - 30 %
Treated Filler	68611-44-9	10 - 30 %
Dimethylpolysiloxane	70131-67-8	60 - 90 %

**4. FIRST AID MEASURES**

**INGESTION**

Do not induce vomiting. Slowly dilute with 1-2 glasses of water or milk and seek medical attention. Never give anything by mouth to an unconscious person.

**SKIN**

Wash with soap and water. Get medical attention if irritation or symptoms from Section 3 develop.

**INHALATION**

If inhaled, remove to fresh air. If not breathing give artificial respiration using a barrier device. If breathing is difficult give oxygen. Get medical attention.

**EYES**

In case of contact, immediately flush eyes with plenty of water for at least 15 minutes and get medical attention if irritation persists.

**NOTE TO PHYSICIAN**

None known.



**SCS1203 12R-Crtrg (0.730 Lbs-0.331 Kg)**  
**Silicone sealant (adhesive)**

**5. FIRE-FIGHTING MEASURES**

**FLASH POINT:** > 93.3 °C; 200 °F  
**METHOD:** estimated  
**IGNITION TEMPERATURE:** Not applicable  
**FLAMMABLE LIMITS IN AIR - LOWER (%):** Not applicable  
**FLAMMABLE LIMITS IN AIR - UPPER (%):** Not applicable

**SENSITIVITY TO MECHANICAL IMPACT:** No

**SENSITIVITY TO STATIC DISCHARGE**  
Sensitivity to static discharge is not expected.

**EXTINGUISHING MEDIA**  
All standard extinguishing agents are suitable.

**SPECIAL FIRE FIGHTING PROCEDURES**  
Firefighters must wear NIOSH/MSHA approved positive pressure self-contained breathing apparatus with full face mask and full protective clothing.

**6. ACCIDENTAL RELEASE MEASURES**

**ACTION TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED**  
Wipe, scrape or soak up in an inert material and put in a container for disposal. Wash walking surfaces with detergent and water to reduce slipping hazard. Wear proper protective equipment as specified in the protective equipment section.

**7. HANDLING AND STORAGE**

**PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE**  
Avoid contact with skin, eyes and clothing. Use only in well-ventilated areas. Avoid accidental ingestion of this material. Wash hands and face before eating, drinking, smoking, using toilet facilities, or applying cosmetics. Remove contact lenses before using sealant. Do not handle lenses until all sealant has been cleaned from the fingertips, nails and cuticles. Residual sealant may remain on fingers for several days and transfer to lenses and cause severe eye irritation. Store away from heat, sources of ignition, and incompatibles. Keep away from children. Keep container closed when not in use.

**STORAGE**  
Keep containers tightly closed in a cool, well-ventilated place.



**SCS1203 12R-Crtrg (0.730 Lbs-0.331 Kg)**  
**Silicone sealant (adhesive)**

**8. EXPOSURE CONTROLS / PERSONAL PROTECTION**

**ENGINEERING CONTROLS**

Eyewash stations; Showers; Exhaust ventilation

**RESPIRATORY PROTECTION**

If exposure limits are exceeded or respiratory irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Supplied air respirators may be required for non-routine or emergency situations. Respiratory protection must be provided in accordance with OSHA regulations (see 29CFR 1910.134).

**PROTECTIVE GLOVES**

Cloth gloves.

**EYE AND FACE PROTECTION**

Monogoggles.

**OTHER PROTECTIVE EQUIPMENT**

Wear suitable protective clothing and eye/face protection.

**Exposure Guidelines**

<u>Component</u>	<u>CAS RN</u>	<u>Source</u>	<u>Value</u>
------------------	---------------	---------------	--------------

Absence of values indicates none found

PEL - OSHA Permissible Exposure Limit; TLV - ACGIH Threshold Limit Value; TWA - Time Weighted Average

OSHA revoked the Final Rule Limits of January 19, 1989 in response to the 11th Circuit Court of Appeals decision (AFL-CIO v. OSHA) effective June 30, 1993. See 29 CFR 1910.1000 (58 FR 35338).

**9. PHYSICAL AND CHEMICAL PROPERTIES**

<b>BOILING POINT - C &amp; F:</b>	Not applicable
<b>VAPOR PRESSURE (20 C) (MM HG):</b>	No data available
<b>VAPOR DENSITY (AIR=1):</b>	Not applicable
<b>FREEZING POINT:</b>	Not applicable
<b>MELTING POINT:</b>	Not applicable
<b>PHYSICAL STATE:</b>	Solid
<b>ODOR:</b>	vinegar-like
<b>COLOR:</b>	Black
<b>EVAPORATION RATE (BUTYL ACETATE=1):</b>	< 1
<b>SPECIFIC GRAVITY (WATER=1):</b>	ca. 1.06
<b>DENSITY:</b>	ca. 1.06 g/cm <sup>3</sup>
<b>ACID / ALKALINITY (MEQ/G):</b>	Not applicable
<b>pH:</b>	Not applicable
<b>VOLATILE ORGANIC CONTENT (VOL):</b>	2.1 %(m)
<b>SOLUBILITY IN WATER (20 C):</b>	Insoluble
<b>SOLUBILITY IN ORGANIC SOLVENT (STATE)</b>	Toluene



**SCS1203 12R-Crtrg (0.730 Lbs-0.331 Kg)**  
**Silicone sealant (adhesive)**

**SOLVENT):**  
**VOC EXCL. H2O & EXEMPTS (G/L):** 23

**10. STABILITY AND REACTIVITY**

**STABILITY**  
Stable

**HAZARDOUS POLYMERIZATION**  
Will not occur.

**HAZARDOUS THERMAL DECOMPOSITION / COMBUSTION PRODUCTS**  
Carbon monoxide; Carbon dioxide (CO<sub>2</sub>); Silicon dioxide.; Formaldehyde

**INCOMPATIBILITY (MATERIALS TO AVOID)**  
No data available

**CONDITIONS TO AVOID**  
None known.

**11. TOXICOLOGICAL INFORMATION**

**ACUTE ORAL**  
Remarks: No data available

**ACUTE DERMAL**  
Remarks: No data available

**ACUTE INHALATION**  
Remarks: No data available

**OTHER**  
Octamethylcyclotetrasiloxane Ingestion: Rodents given large doses via oral gavage of octamethylcyclotetrasiloxane (1600 mg/kg day, 14 days) developed increased liver weights relative to unexposed control animals due to hepatocellular hyperplasia (increased number of liver cells which appear normal) as well as hypertrophy (increased cell size). Inhalation: In inhalation studies, laboratory rodents exposed to octamethylcyclotetrasiloxane (300 ppm five days week, 90 days) developed increased liver weights in female animals relative to unexposed control animals. When the exposure was stopped, liver weights returned to normal. Microscopic examination of the liver cells did not show any evidence of pathology. Inhalation studies utilizing laboratory rabbits and guinea pigs showed no effects on liver weights. Inhalation exposures typical of industrial usage (5-10 ppm) showed no toxic effects in rodents. Range finding reproductive studies were conducted (whole body inhalation, 70 days prior to mating, through mating, gestation and lactation) with octamethylcyclotetrasiloxane (D4). Rats were exposed to 70 and 700 ppm. In the 700 ppm group, there was a statistically significant reduction in mean litter size and in implantation sites. No D4 related clinical signs were observed in the pups and no exposure related pathological findings were



**SCS1203 12R-Crtrg (0.730 Lbs-0.331 Kg)**  
**Silicone sealant (adhesive)**

---

found. Interim results from a two generation reproductive study in rats exposed to 500 and 700 ppm D4 (whole body inhalation, 70 days prior to mating, through mating, gestation and lactation) resulted in a statistically significant decrease in live mean litter size as well as extended periods of off-spring delivery (dystocia). These results were not observed at the 70 and 300 ppm dosing levels. Preliminary results from an ongoing 24-month combined chronic/oncogenicity study in rats exposed to 10, 30, 150, or 700 ppm D4 showed test-article related effects in the kidney (male and female) and uterus of rats exposed for 12 to 24 months. These effects include increased kidney weight and severity of chronic nephropathy, increased uterine weight, increased incidence of endometrial cell hyperplasia, and an increased incidence of endometrial adenomas. All of these effects are limited to the 700 ppm exposure group. The relevance of these data to humans is unclear. Further studies are ongoing. In developmental toxicity studies, rats and rabbits were exposed to octamethylcyclotetrasiloxane at concentrations up to 700 ppm and 500 ppm respectively. No teratogenic effects (birth defects) were observed in either study.

**SENSITIZATION**

No data available

**SKIN IRRITATION**

No data available

**EYE IRRITATION**

No data available

**MUTAGENICITY**

Unknown

**OTHER EFFECTS OF OVEREXPOSURE**

Acetic acid released during curing.

**12. ECOLOGICAL INFORMATION**

**ECOTOXICITY**

Ecotoxicological data for this product is not available.

**DISTRIBUTION**

No data available

**CHEMICAL FATE**

No data available

**13. DISPOSAL CONSIDERATIONS**

**DISPOSAL METHOD**

Disposal should be made in accordance with federal, state and local regulations.



**SCS1203 12R-Crtrg (0.730 Lbs-0.331 Kg)  
Silicone sealant (adhesive)**

**14. TRANSPORT INFORMATION**

**Further Information:** This product is not regarded as dangerous goods according to the national and international regulations on the transport of dangerous goods.

**15. REGULATORY INFORMATION**

**Inventories**

Canada DSL Inventory	y (Positive listing)	
Japan Inventory of Existing & New Chemical Substances (ENCS)	y (Positive listing)	
Korea Existing Chemicals Inventory (KECI)	y (Positive listing)	
China Inventory of Existing Chemical Substances	y (Positive listing)	
Australia Inventory of Chemical Substances (AICS)	y (Positive listing)	
Philippines Inventory of Chemicals and Chemical Substances (PICCS)	y (Positive listing)	
TSCA list	y (Positive listing)	On TSCA Inventory
EU list of existing chemical substances	y (Positive listing)	
Canada NDSL Inventory	n (Negative listing)	

For inventories that are marked as quantity restricted or special cases, please contact Momentive.

**US Regulatory Information**

**SARA (311,312) HAZARD CLASS**

Acute Health Hazard; Chronic Health Hazard

**SARA (313) CHEMICALS**

**Canadian Regulatory Information**

**WHMIS HAZARD CLASS**

D2A VERY TOXIC MATERIALS, D2B TOXIC MATERIALS

**Other**

**SCHDLE B/HTSUS:** 3214.10.00.10 Mastic based on rubber



**MOMENTIVE**  
performance materials

## Material Safety Data Sheet

Version: 1.5  
09/05/2007

### **SCS1203 12R-Crtrg (0.730 Lbs-0.331 Kg) Silicone sealant (adhesive)**

---

ECCN:

EAR99

#### **CALIFORNIA PROPOSITION 65**

This product does not contain any chemicals known to State of California to cause cancer, birth, or any other reproductive defects.

### **16. OTHER INFORMATION**

#### **OTHER**

These data are offered in good faith as typical values and not as product specifications. No warranty, either expressed or implied, is made. The recommended industrial hygiene and safe handling procedures are believed to be generally applicable. However, each user should review these recommendations in the specific context of the intended use and determine whether they are appropriate., C = ceiling limit NEGL = negligible EST = estimated NF = none found  
NA = not applicable UNKN = unknown NE = none established REC = recommended ND = none determined V = recommended by vendor SKN = skin TS = trade secret R = recommended MST = mist NT = not tested STEL = short term exposure limit ppm = parts per million ppb = parts per billion By-product= reaction by-product, TSCA inventory status not required under 40 CFR part 720.30(h-2).